

MITSUBISHI L200 SINGLE CAB - TECHNICAL SPECIFICATION



MODEL	L200 Single Cab 2.5 DI-D 4WD 5-Speed Manual
-------	---

DIMENSIONS & WEIGHTS	
Overall Length (mm)	5,040
Overall Width (mm)	1,750
Overall Height (mm)	1,775
Wheelbase (mm)	3,000
Track	
Front (mm)	1,505
Rear (mm)	1,500
Bed Interior Length (mm)	2,220
Bed Interior Width (mm)	1,470
Bed Interior Height (mm)	405
Min. Ground Clearance (mm)	200
Cargo Floor Height (mm)	845
Curb Weight (kg)	1,745
Gross Vehicle Weight (kg)	2,890
Payload (kg)	1095~1145
Max. Axle Load	
Front (kg)	1,260
Rear (kg)	1,800
Minimum Turning Radius (m)	5.9
Towing Capacity	
with brake (kg)	3,000
w/o brake (kg)	750
Seating Capacity (persons)	2

ENGINE	
Type	4D56 DI-D Common-Rail I/C T/C
Construction	Longitudinally mounted 4-cylinder, 4-stroke Turbo diesel direct injection engine with intercooler. 4 valves per cylinder
Total Displacement (cc)	2,477
Bore x Stroke (mm)	91.1 x 95.0
Injection System	Electronic Common-Rail direct injection with centrally mounted injection valves
Emission Level	Euro5b (EURO 5+)
Compression Ratio	16.5:1
Max Output (kW(PS)/rpm)	100 (134) / 4,000
Max Torque (Nm/rpm)	314 / 1,500-2,680

PERFORMANCE	
Fuel Economy (l/100km)	
Urban	8.7
Extra-urban	6.7
Combined	7.4
CO2 Emissions (g/km)	195
Acceleration, 0-100 km/h (sec)	9.2
Max. Speed (km/h)	167

FUEL SYSTEM	
Fuel Type	Diesel
Fuel Tank Capacity (litre)	75

TRANSMISSION	
Clutch	Single, dry plate with diaphragm spring
Type	5-speed manual
Gear Ratio	
1st	4.313
2nd	2.330
3rd	1.436
4th	1.000
5th	0.788
Reverse	4.220
Transfer Gear Ratio	
High	1.000
Low	1.900
Final Gear Ratio	3.917

STEERING	
Type	Rack & pinion with power steering

SUSPENSION	
Front	Independent wishbone, coil springs
Rear	Rigid axle, elliptic leaf springs

BRAKES	
Front	Ventilated discs 16"
Rear	Leading & trailing drums 11.6"